

**BITUMINOUS ALUMINIUM PAINT**

**A HEAT AND UV REFLECTIVE COATING FOR ASPHALT, BITUMEN, CONCRETE AND METALLIC SURFACES  
MAINTENANCE COATING FOR BUILT-UP WATERPROOFING SYSTEMS**

**PRINCIPAL USES**

As a decorative reflective coating on all bituminous systems and roof repairs.

**SPECIFICATION**

All surfaces to be coated with Pro-Struct 202 must be clean, sound and dry. All areas must be free from oils and grease.

**INSTRUCTIONS**

Concrete and bituminous surfaces must be primed with Pro-Struct 201 Primer. Refer to Product Data Sheets for preparation of surfaces. Apply by brush or roller.

**MIXING**

Stir well. Aluminium flakes will settle and the product must be continuously stirred. Adequate ventilation must be allowed for and do not smoke or use naked flame during application.

**CLEANING**

Clean equipment with Pro-Struct 105 Epoxy Brush Cleaner and rinse off with water.

**TYPICAL PROPERTIES AT 25°C**

<b>Colour</b>	Aluminium
<b>Shelf Life</b>	12 Months
<b>Coverage recommend</b>	6-10m <sup>2</sup> /litre, two coats
<b>Flash Point</b>	35°C
<b>Consistency</b>	Thin liquid
<b>Drying Time</b>	2-4 Hours
<b>Volume Solids</b>	35%
<b>Application</b>	Brush, roller or spray
<b>Application Temperature Range</b>	10°C to 35°C
<b>Water Resistance</b>	Not recommended for total immersion
<b>Solvent Resistance bitumen</b>	Solvents will attack
<b>Safety: Material is flammable and the necessary safety precautions need to be taken in the handling of his product.</b>	