

HIGH SHEEN COATING

**HIGH SHEEN SMOOTH FINISH
DURABLE
LOW DIRT RETENTION – EASY TO CLEAN
ANTI-FUNGAL COATING
EXCELLENT ADHESION
PROTECTS SURFACES FROM WATER INGRESS**

PRINCIPAL USES

A tough, durable interior or exterior high build wall coating designed to protect fibreboard, plaster, masonry, wood and galvanised surfaces from wear and extreme weather conditions. It is particularly recommended for new or previously coated surfaces in areas exposed to wet, high humidity conditions as well as areas needing continual cleaning, e.g. food and beverage processing, office blocks, flats, schools, hospitals, factories and hotels.

RESISTANCE

Exceptional resistance to intense UV, water, hail, cyclic temperature changes and substrate alkali attack. Completely unaffected by industrial fallout and detergent washing.

SPECIFICATION

Prepare surface and apply a minimum of two coats Pro-Struct 684/6 High Sheen Coating in accordance with Manufacturer's detailed instructions.

INSTRUCTIONS

Prior to application all surfaces to be clean, dry and sound. Prime with Pro-Struct 689 Masonry Primer at 6 to 8m²/litre followed by two or more coats of Pro-Struct 684/6 High Sheen Coating at 7-9m²/litre/coat, allowing 6-8 hours drying between coats.

TYPICAL PROPERTIES AT 25°C

Finish	High Sheen
Colour	White and limited range Available
Type	Adhesion promoted acrylic
Volume Solids	40-42%
Theoretical Coverage	7-9m ² /litre/coat
Apply Over	Dust and oil-free masonry, wood and galvanized steel surfaces
Apply By	Brush, roller or spray
Drying Time	6-8 Hours
Thinner	Water
Shelf Life	12 Months
Application Temperature Range	10°C-35°C
Carbon Dioxide Diffusion Resistance, RCO ²	Greater than 50m
Water Vapour Diffusion RH ₂ O	Less than 4m