

ALKALI RESISTANT PENETRATION PRIMER

**SOLUTION COATING WITH DEEP PENETRATING PROPERTIES
VAPOUR PERMEABLE FILM ALLOWING BREATHABILITY
EXCELLENT ADHESION TO POROUS SUBSTRATES
RESISTS MILDEW AND FUNGUS GROWTH**

PRINCIPAL USES

A high quality wall coating ideal for porous substrates such as new and old plaster, fibreboard and concrete surfaces. Ideal as a primer for subsequent coats of high quality adhesion promoted acrylic paints such as Pro-Struct 684/4 Muralflex and Pro-Struct 684/6.

RESISTANCE

Excellent resistance to substrate alkali attack, severe weather conditions, mildew and fungus growth and general household detergent washing.

INSTRUCTIONS

All surfaces to be sound, clean and dry before application.

On freshly plastered surfaces, allow plaster to dry out and remove dust before application. If substrates are very porous, they should be sealed by diluting Pro-Struct 689 with 10% Carboline Thinner # 10 prior to coating. Apply 2 or 3 coats by brush, roller or airless spray at the following spread rates:

- Flat surfaces using a medium nap roller : 6-8m²/litre/coat
- Rough irregular surfaces using a brush or spray : 4-6m²/litre/coat

TYPICAL PROPERTIES AT 25°C

Type	Solution Masonry Paint
Finish	Slight textured matt finish
Colour	White
Drying Time	3-4 hours at 25°C
Overcoat Time	4 Hours at 25°C
Spread Rate	6-8m ² /litre on flat surfaces
Application	Brush, roller or airless spray
Cleaner	Pro-Struct 105 Brush Cleaner
Shelf Life	12 Months