

ANTIQUE FINISH Product No. PS3631

Ritver Antique finish is a top of the line water based finish whose looks brings history to the present day era. It exhibits a finish very much akin to the historical concepts of the paintings and enhances the richness of the exteriors of buildings with a traditional look. It creates a rough but appealing finish and can end up in different patterns utilizing the imagination of an artist and the skills of the applicator. on practically any surface. The product can be over coated with good quality exterior emulsion colours to give a pleasing look. The product is very hygenic and has good anti fungal properties. The maintenance cost is low. The product has virtually long life and can withstands extreme conditions as it can be coated to good thickness.

USE

Substrates: Concrete, plaster, masonry, gypsum.

Area of Use: Interiors with ability to overcoat if needed.

SPECIFICATIONS

Properties

| | |
|--|---|
| Finish | : Pough and plaster like |
| Colour | : Natural colours of earth resembling the traditional soil. |
| Specific gravity | : 1.8 ± 0.02 |
| Solids (% by volume) | : 58 ± 2 |
| Diluent | : Sweet Water |
| Flash point | : Not Applicable |
| Spread Rate: | |
| While the spread rate is directly dependant on the surface profile, the pattern required and also the type of undulations it has, as a thumb rule Ritver Antique finish would cover app 1.0 to 1.5 sq mtrs per Kg, and may be taken for cost calculations. (The coverage is not very significant as it can be applied to varying thickness. | |
| Drying Time (30° C) | : Set to touch: 2 – 3 hours. : Ready for Recoat: at touch dry stage. |
| Recommended DFT | : Thickness can be achieved as per requirement. |

SURFACE PREPARATION

A good surface preparation and following the method statement / recommended system procedure of Ritver is an ideal recommendation for the application **Ritver Antique finish**

Exclusions for successful application include perpetually wet surfaces and also large cavities on wood, metal & concrete surfaces.

Ensure the surface is clean, dry & free from all loose or flaking particles. **Apply Ritver all weather Tex Primer** or **Ritver AR Primer** for the concerned substrate. Allow it to dry and keep the same ready for the forthcoming coats of **RitverAntique finish**.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.

ANTIQUE FINISH Product No. PS3631

APPLICATION METHODS

Adequate ventilation is an ideal situation as it helps in drying and the good application itself. Avoid high humid conditions i.e., >95% when condensation is likely to interfere and also when the surface temperature is at least 3°C above dew point.

One can add minimum quantity of sweet water for getting the right consistency depending on the speed and skill of the applicator. One should apply with a putty knife or a broad bladed knife and spread it evenly to the desired pattern. Allow to dry and then repeat the applications to the desired thickness. It is advisable to build up the quote with nominal thickness per application. This would ensure proper cure and capability of drying without cracks.

If coloring is required use a natural colour of **Ritver Antique finish** and apply a good layer of good quality external emulsion as per the desired colour.

TYPICAL PAINT SYSTEM

| | | |
|---|--|--|
| <p>Ritver Antique Finish</p> <ul style="list-style-type: none"> Or as per Ritver technical advice | <p>Ritver All Acrylic Primer Ritver Antique Finish Ritver All Acrylic Topcoat</p> | <p>1 coat 1 – 2 coats 1 coat</p> |
|---|--|--|

STORAGE & SHELF LIFE

Under dry and cool condition, storage stability can be sound up to 18 months in original sealed containers.

HANDLING

Disposal: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Flash Point: Not applicable

SAFETY PRECAUTION

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray. MSDS is available on request for the safe handling of this product.

FIRST AID

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved Industrial cleaner. DO NOT USE solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.