

STUCCO PUTTY WHITE

Product No. **PW2503**

Ritver Stucco Putty is based on an acrylic copolymer formulated with pigments with good alkali resistant pigments. It is primarily used for filling surface irregularities, construction flaws, hairline surface cracks & indentations. The surface is rendered smooth and leveled with enough anchorage so as to apply a smooth layer of subsequent coats.

USE

Substates: Concrete, plaster, masonry, gypsum, and wood works.

Area of Use: Interior and Exterior use

SPECIFICATIONS

Properties

Finish	: Smooth & Buttery.
Colour	: White
Specific gravity	: 1.69 ± .05
Solids (% by volume)	: 42 ± 1%
Diluent	: Sweet Water
Flash point	: Not Applicable

Spread rate:

While the spread rate is directly dependent on the surface profile and also the type of undulations it has. As a thumb rule of Ritver Stucco Putty would cover 3 sq. meters per liter @ 150 microns. And maybe taken for cost calculations.

Drying Time (30° C)	: Set to touch: 1 – 2 hours. Ready to recoat : App 6-8 hrs.
----------------------------	--

Recommended DFT: **1-2 coats: App 100-150mic. Per coat**

SURFACE PREPARATION

A good surface preparation and following the method statement / recommended system procedure of Ritver is an ideal recommendation for the application of Ritver Stucco Putty.

For Plaster, Masonry & Concrete

Achieve a good and clean surface by removing all contaminants by cleaning & drying. A laitance free surface should be achieved by good sweep blast or a wire brush.

Before applying the Ritver Stucco putty apply one coat of Ritver PVA Primer Sealer and allow drying.

For Wood & Timber

Achieve a good and clean surface by removing all contaminants by cleaning & drying treatment with Ritver Wood Preservative compound is advisable. Start off with a good coat of Ritver Wood Primer and allow to dry well.

Exclusions for successful application include perpetually wet surfaces and also large cavities on wooden surfaces.

RITVER EXTERIOR PUTTY Product No. PW2507

Adequate ventilation is an ideal situation as it helps in drying and the good application itself. Avoid high humid conditions i.e., >95% when condensation is likely to interfere and also when the surface temperature is at least 3°C above dew point. One can add 5 to 10% of sweet water for ease of application depending on the suitability of application. One should apply with a putty knife or a broad bladed knife and spread it evenly on the surface to smoothen. After application light sanding may be done to remove the imperfections.

TYPICAL PAINT SYSTEM

Ritver Stucco Putty White	Ritver PVA Primer Sealer	1 coat
	Ritver Stucco Putty	2 coats
Recommended system to be applied as per surface preparation. (Suitable emulsion grades)	Ritver Emulsion (Gold)	2 coats

- Or as per Ritver technical advice

STORAGE & SHELF LIFE

Storage and Shelf Life

Under dry and cool condition, storage stability can be sound up to 18 months in original sealed containers.

Handling

Disposal: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Flash Point: Not applicable.

SAFETY PRECAUTION

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream. Other industrial practices are applicable. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.

MSDS is available on request for the safe handling of this product.

FIRST AID

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE Solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.