

ATMOSPHERA Product No. PW3629

Atmosfera is a top of the range specially formulated acrylic emulsion based latex coating pigmented system with the right properties to build various decorative patterns. Its good virtues include good wash ability, superior scrub resistance, smooth finish, colour acceptance & retention property and a superior finish. Its unique formula is specially prepared to match ambience of the interiors and decorations thereof.

USE

Substrates: Concrete, cement plaster, masonry, gypsum, block work etc.

Area of Use: Interiors decorations.

SPECIFICATIONS

Properties

Finish	: Rough and matt
Colour	: White base to be mixed with the color tubes as per the requirement of the customer.
Specific gravity	: 1.03 ± 0.05
Solids (% by volume)	: 16 ± 2
Diluent	: Sweet Water
Flash point	: Not Applicable
Spread Rate:	
While the spread rate is directly dependant on the extend of decoration sought and also the surface profile, Sandica would cover app 6 to 8 m ² /liter at 30 – 40 microns per coat.	
Drying Time (30° C)	: Set to touch: 1 – 2 hours. : Ready for Recoat: app 2 - 3 hours.
Recommended DFT	: As per need. App 30 – 40 mic per coat.

SURFACE PREPARATION

A good surface preparation and following the method statement / recommended system procedure of is an ideal recommendation for the application of **Atmosfera**.

For Plaster, Masonry & Concrete:

Achieve a good and clean surface by removing all contaminants and loose particles by cleaning & drying. A laitance free surface should be achieved by good sweep blast or a wire brush. Water washing under pressure is recommended. Apply the **Alkali resistant primer or Tex primer** and allow drying as per the data sheet and subject to one more coat for even coverage. Apply a good coat of **Satin emulsion** in the desired shade. After drying either apply the clear Patina or mix it with the colour stain and apply evenly with hand aided with a special glove, sponge or any other decorative application aid. A long bristle brush can also be used for giving the desired pattern. For patterns involving more than one colour, use them in sequence.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.

Date Revised: 01st Jan 2012

ATMOSPHERA Product No. PW3629

APPLICATION METHODS

Adequate ventilation is an ideal situation as it helps in drying and the good application itself. Avoid high humid conditions i.e., >95% when condensation is likely to interfere and also when the surface temperature is at least 3°C above dew point.

- Dilution:** One can add 5 to 10% of sweet water for ease of application depending on the suitability of application.
- Brush:** Long bristle brush as per the convenience of the applicator.
- Special painting tools:** By means of sponge, rags, gloves or any other fancy tools by spreading uniformly and avoid excess paint to spoil the pattern.

TYPICAL PAINT SYSTEM

<p>Ritver Atmosfera</p> <p>Recommended system to be applied as per surface preparation.</p> <ul style="list-style-type: none"> Or as per Ritver technical advice 	<p>Ritver Primer Sealer Ritver Stucco Putty Ritver Platinum Emulsion Ritver Atmosfera</p>	<p>1 coat 2 coats 1 coat 1 coat</p>
--	--	---

STORAGE & SHELF LIFE

Under dry and cool condition, storage stability can be sound up to 12 months in original sealed containers.

HANDLING

Disposal: As per the guidance and legislations of the local Authority e.g., by controlled landfill. In case of doubt, consult local authority. Do not empty into drains, sewers or other water courses.

Flash Point: Not applicable.

SAFETY PRECAUTION

Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.

Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.

MSDS is available on request for the safe handling of this product.

FIRST AID

Eyes: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin: Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.

Inhalation: Remove to fresh air, loosen collar and keep patient rested.

Ingestion: In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate and application, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact RITVER Technical Service Department.

Date Revised: 01st Jan 2012