

PU TOPCOAT CLEAR – [MATT] Product No. **PT 28X0** [Light Grade]

Light grade two components Polyurethane Topcoat, formulated with solid content combined with fast drying, very good transparency, flow, and leveling characteristics, provides the excellent equalization of the matt effect. Combined with the high mechanical resistant and soft slippery touch that enhances the overall beauty and feasibility of the finishing product.

USES

For interior use on all furnishings as wardrobes, closet, paneling, doors, windows, frame, and casting, etc. The overall characteristics such as extensibility, Matt effect equalization, transparency and resistance to polishing have been developed to the maximum which in turn enables the product to have almost unlimited possibilities in the furniture industry.

CHARACTERISTICS

Properties

- Light Grade
- Very Good Leveling
- Fast Drying
- Very Good Transparency
- Very Good Flow

Available in the following Shades

- | | | |
|----------|--------|------|
| - PT2800 | DM 6% | [±1] |
| - PT2810 | MT 12% | [±3] |
| - PT2830 | SM 30% | [±5] |
| - PT2850 | SG 50% | [±5] |
| - PT2870 | GL 70% | [±5] |

| | |
|------------------------------|-------------------------|
| Appearance | : Matt |
| Color | : Transparent |
| Specific gravity | : 0, 97 Kg/lit [±0.025] |
| Weight Solids | : Approx. 42% [± 2] |
| Weight Solids blended | : Approx. 35% [± 2] |
| Flash point | : 21°C |
| Drying Time | |
| Dust Free | : 15 min. |
| To Touch | : 30 min. at 25°C |
| Interval Coats | : 3 hrs. at 25°C |
| Deep Drying | : 24 hrs. at 25°C |

PU TOPCOAT CLEAR – [MATT]

Product No. **PT 28X0**

[Light Grade]

CLEANING

Cleaning

Clean all tools and equipment immediately after use with [TC010] Tool Cleaner.

PACKING & STORAGE

Available in 5Ltr, 25Ltr.

Store in a cool and well ventilated place. Keep away from direct sunlight. Minimum one year in unopened container, stored in a cool and dry condition at 25°C.

SAFETY & FLAMMABLE

This material is flammable and must not be exposed to naked flames.

Use only in well ventilated areas. In case of insufficient ventilation during application, wear suitable respiratory equipment. Do not breathe vapor / spray. In case of contact with eyes, rinse immediately with plenty of sweet water and seek medical advice. In case of contact with skin, wash immediately with soap and water or a recognized skin cleanser.

Keep away from sources of ignition. No Smoking. Keep out of reach of children.